

豫昶 LC 系列 CO2 激光喷码机系列

豫昶 LC 系列采用美国原装进口激光器，最先进的偏振镜系统，确保了优异的喷码质量和高速度输出。整个激光系统集成成了触摸屏界面，感应电眼和升降托架。结构设计精巧和紧凑，因此可以在狭小的空间方便安装。LC 系列有着良好的稳定性，性能可靠，主要应用于包装行业，如食品，医药，饮料，日化等

激光整机特性

整机材质: 全铝结构

激光器: CO2

连续输出功率: $\geq 30W$

激光波长: $930 \mu m / 1064 \mu m$

偏转振镜: 高精度双维扫描系统

标刻速度: $\leq 12000mm/s$

主控: 高度集成化主板，内嵌 7 寸屏幕

操作系统: WIN CE

冷却系统: 风冷

激光喷码参数

聚焦镜头: 焦距 $140mm$

打标刻线类型: 点阵、矢量一体机（既可打点阵又可打矢量）

最小线宽: $0.012mm$

重复定位精度: $0.003mm$

打标范围: $110mm \times 110mm$ （可选）

定位方式: 红光定位、对焦

打刻字符行数: 在打标范围内任意行

支持类型:

字体: 中英文，数字，繁体中文等标准字库

文件格式: BMP/DXF/HPGL/JPEG/PLT

条码: CODE39、CODE128、CODE126、QR、真知码

整备参数

电源: $110-240V 50/60HZ$

耗电量: $900W$

机器净重: $70kgs$

外形尺寸: $120X78X34cm$

环境要求: 外部温度 $0^{\circ}C - 45^{\circ}C$; 湿度 $\leq 95\%$; 非冷凝; 无振动

CYCJET LC Series LC30F CO2 Fly Laser Printers

CYCJET LC series fly laser printer uses the US imported lasers, advanced polarizer system to ensure superior quality and high speed marking output. The entire laser system integrates a touch-screen interface, induction electric parts and lift the bracket. Sophisticated and compact design, it can be easily installed in tight spaces. LC series with high stability, reliability, mainly used in chemical, food, beverage, pharmaceutical and other marking.

Laser machine features:

Frame Material: ALUM.

Laser Device: CO2 Laser

Power: $\geq 30W$

Laser Wavelength: 930 μm / 1064 μm

Galvanometer deflection: High Precision dual dimensional scanning system

Marking speed: $\leq 12000mm/s$

Master Control: Highly integrated board with 10 inch Color Touch screen

Operating System: High speed Linux fly Printing Software Software

Cooling: 3groups (6pcs) Cooling Fans

Marking Specifications:

Focus Distance: Focus 145mm

Marking line type: Dot matrix, bold, vector all in one(both dot matrix and vector)

Minimum line width: 0.015mm

Repeatability accurate positioning: 0.003mm

Marking Area: Standard 110mm \times 110mm (Customized available)

Marking height: Standard Character height 110mm

Marking Length: Unlimited

Positioning mode: Red light positioning and focusing

Number of characters: Any line(multi-line) within marking range

Support type:

Typeface: Chinese, English, Arabic, Spanish Font library ;

Marking: Number, logo, image, letter, serials number, system date & time, etc...

File format: BMP/DXF/HPGL/JPEG/PLT

Bar code: CODE39、CODE128、CODE126、QR、Z-Code

Others:

Power Supply: 100-220V/50-60HZ

Power Consumption: 900W

Net Weight: 70kgs

Oversize: 1200mm \times 780mm \times 340mm

Environmental Requirement: 0 $^{\circ}C$ —45 $^{\circ}C$; humidity $\leq 95\%$; non-condensing; no shaking